


SCOPIA XT1000 Series

Never compromise again



First Class Video Experience

Every SCOPIA XT1000 delivers full HD (1080p 30fps) video streams as standard so you don't have to compromise with lower quality video. The included high end PTZ camera supports 10x optical zoom and wide angle capability so you can see every detail as well as an entire group in the conference room. An additional 1080p camera can be used to send a separate 1080p video stream for complete visual coverage.



Hear Every Nuance

The SCOPIA XT1000 3-way microphone pod uses beam forming technology to put the focus on the speaker while isolating background noise. Two microphone pods can also be cascaded to cover larger rooms. 48 kHz (full band) audio encoding is used to ensure high clarity audio transmission with no loss of quality.



Crisp, High Motion Data Sharing

Finally, remote participants can view your shared data as if they are in the same room with you in all its native detail. The SCOPIA XT1000 supports PC data sharing at 1080p 30fps so you can share presentations and even video clips with zero loss of quality.



Embedded HD Multi-party Conferencing

RADVISION's multi-party expertise is now embedded in the SCOPIA XT1000. High Definition, Continuous Presence meetings with up to 9 participants are now more affordable than ever utilizing the SCOPIA XT1000 built in MCU.



State of the Art Total Solution

The SCOPIA XT1000 room system complements RADVISION's innovative total video conferencing solution, including the VC240, a disruptive all-in-one HD desktop system, the SCOPIA Elite MCU offering multipoint power and scale, SCOPIA Desktop enabling HD conferencing on the go, and the SCOPIA Management Suite for deploying and managing distributed video conferencing deployments. With RADVISION's total solution you can enjoy a seamlessly integrated complete visual communications system.



Specifications

Communications

- IP: H.323, SIP (RFC 3261)
- ISDN^{1,2}: H.320
- Bit rate: H.323, SIP: up to 4/12¹ Mbps
H.320: up to 2 Mbps
- MCU compatibility: H.243, H.231

Video

- Support for 2 simultaneous 1080p30 channels: camera + auxiliary camera¹ or camera + content
- H.261, H.263, H.263+, H.263++, H.264, H.264 SVC²
- Dual Video: H.239 (H.323); BFCP (SIP)
- **Video Resolutions:**
1920 x 1080@30fps: HD1080p30
1280 x 720@60fps: HD 720p60^{2,3}
1280 x 720@30fps: HD 720p30
1024 x 576@30fps: w576p
768 x 448@30fps: w448p
512 x 288@30fps: wCIF
352 x 288@30fps: CIF
352 x 240@30fps: SIF
- **Content Resolutions:**
1920 x 1200@30fps: WUXGA
1600 x 1200@30fps: UXGA
1440 x 900@30fps: WSXGA
1280 x 1024@30fps: SXGA
1280 x 768@30fps: WXGA
1024 x 768@30fps: XGA
800 x 600@30fps: SVGA
640 x 480@30fps: VGA

HD Camera

- Resolution: 1920 x 1080
- Presets: 122
- Field of View (horizontal): 8° - 74°
- PAN / Tilt: ± 100° / ± 25°
- Zoom: 10x (optical)
- Far End Camera Control: H.224, H.281
- Support for Sony® EVI HD7 Camera^{1,2}

Audio

- Acoustic echo cancellation
- Adaptive post filtering
- Audio error concealment
- Automatic Gain Control (AGC)
- Automatic noise suppression
- Frequency Response:
G.711: 300 – 3,400 Hz
G.728: 50 – 3,400 Hz¹
G.729A: 50 – 3,400 Hz
G.722: 50 – 7,000 Hz
G.722.1: 50 – 7,000 Hz
G.722.1 Annex C: 50 – 14,000 Hz
G.719: 50 – 20,000 Hz
AAC-LD: 50 – 20,000 Hz

Digital Microphone Array Pod

- 360° Range
- Frequency Response: 50 – 22,000 Hz
- Mute button
- Up to 2 cascaded pods

Audio/Video Interfaces

- **Video inputs:**
2 x HDMI (Up to 1080p30)
1 x DVI-I (Up to 1920x1200 WUXGA, includes VGA cable adapter)
- **Video outputs:**
2 x HDMI (Up to 1080p30) for dual display
- **Audio inputs:**
2 x HDMI
1 x SPDIF (RCA)
1 x Microphone Array Pod (RJ-11)
- **Audio outputs:**
2 x HDMI
1 x SPDIF (RCA)

Network Features

- IPv4 and IPv6 simultaneous support
- Auto Gatekeeper discovery
- QoS support: IP Precedence, IP Type of Service (ToS)
- IP adaptive packet management including:
Flow control
Packet Loss based down-speeding
Packet Loss recovery policies
- DTMF tones: H.245, RFC2833
- SNTP date and time synchronization

Network Protocols

- TCP/IP, TELNET, HTTP, HTTPS, DNS, DHCP, RTP/RTCP, STUN, SNTP, TFTP

Network Interfaces

- 1 x 10/100 Base-T full-duplex (RJ-45)
- 1 x 10/100/1000 Base-T full-duplex (RJ-45)
- 1 x XLNA for optional network interface

Firewall Traversal

- Auto NAT discovery HTTP and STUN
- H.460.18, H.460.19
- "Keep Alive" packet time configurable

Auxiliary Camera Interface

- VISCA RS232 for PTZ camera control (Mini-DIN 8-pin)

User Interface

- 21 language on-screen user interface
- Infrared remote control
- API for customization (XML)

Directory Service & Address Book

- LDAP Client (H.350)
- Receive global address book from LDAP Server including iVIEW

Embedded HD Multipoint Control Unit¹

- H.323, SIP and H.320 mixed mode
- 4 / 9 HD Continuous Presence participants
- Dial-in / Dial-out capabilities

- Encryption (MCU4)
- Automatic Continuous Presence layouts
- Dual-video from any site (H.323, H.320)

Security Features

- Embedded encryption
- Key generation and exchange with Public-Key Cryptography (Diffie-Hellman), (H.323, SIP)
- H.235 AES 128 Confidentiality for RTP media
- H.235 MD5 Authentication
- H.235 Authentication and Integrity (H.235v3/Annex D)
- Digest Authentication
- Microsoft NTLM Authentication and Session Security (SSP)
- HTTPS, SSH
- Selective Enable / Disable of IP features

Web Management

- Configuration, call, diagnostics and management functions are accessible with:
Internet Explorer™7.0+,
Firefox 3.0[®]+,
Safari 3.0[®]+

Options

- 4 Port Embedded MCU
- 9 Port Embedded MCU
- Additional 1080p 30fps Camera
- Sony® EVI HD7 1080p 30fps / 720p 60fps Camera²
- Additional Digital Microphone Array Pod
- ISDN 6-BRI Network Interface²
- ISDN PRI Network Interface²
- V.35 Network Interface²
- 12 Mbps Extended IP Bit Rate


Power Supply

- 100 - 240 VAC, 50-60 Hz, 2.5 A Max.

Physical Characteristics

- Horizontal Mounting:
W: 37.8 cm (14.9")
H: 5.0 cm (2.0")
D: 18.3 cm (7.2")
Weight: 3.3 kg (7.3 lb)
- Vertical Mounting with Pedestal:
W: 16.1 cm (6.3")
H: 39.8 cm (15.7")
D: 20.5 cm (8.1")
Weight: 3.9 kg (8.6 lb)
- Camera:
W: 15.3 cm (6.0")
H: 18.0 cm (7.1")
D: 15.6 cm (6.1")
Weight: 1.3 kg (2.9 lb)
- Microphone Pod:
W: 14.0 cm (5.5")
Weight: 0.3 kg (0.7 lb)

1. Optional
2. Available with a future firmware release
3. 720p60 receive standard, transmit requires optional camera



About RADVISION

RADVISION (NASDAQ: RVSN) is the industry's leading provider of market-proven products and technologies for unified visual communications over IP and 3G networks. With its complete set of standards based video networking infrastructure and developer toolkits for voice, video, data and wireless communications, RADVISION is driving the unified communications evolution by combining the power of video, voice, data and wireless – for high definition video conferencing systems, innovative converged mobile services, and highly scalable video-enabled desktop platforms on IP, 3G and emerging next generation networks. For more information about RADVISION, visit www.radvision.com